

# Fluoro GS 115-RC

## PTFE Micropowder

Fluoro GS designates a series of powders are made from unsintered, suspension grade virgin PTFE. The products in this series are characterized by the uniform, crystalline structure of PTFE with increased slip and abrasion properties.

### **Product Description:**

Fluoro GS 115-RC is a high molecular weight polytetrafluoroethylene (PTFE) micropowder with an average particle size between 4 and 6  $\mu$ m. This product is produced to be in compliance with EU regulatory requirements.

#### **Applications:**

This product can be used in aviation, military, and food grade grease applications for thickening and/or as an anti-wear additive.

#### **Features and Benefits:**

Thickener

Food Grade

Improves COF

## **Typical Properties:**

Appearance: White Odorless Powder

🔭 Particle Size Mean Value: 4 - 6 μm

\* Cone Penetration: 320 – 400 1/10mm

DSC Melting Point: 325 - 330 °C

#### **Regulatory Status:**

This product is HX-1 and HX-2 registered with NSF. The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS. This product complies with the Commission Delegated Regulation (EU) 2020/784 amending Annex I to POPs Regulation (EU) 2019/1021 (per Shamrock QSOP-202E).

#### Safety, Shipping and Handling:

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

For **more** information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com.

Corporate Headquarters Foot of Pacific Street Newark, NJ 07114 Phone: +1(800)349-1822 Henderson, KY 301 Community Drive Henderson, KY 42420 Phone: +1(800)349-1822 Tongeren, Belgium Heersterveldweg 21, B-3700 Tongeren Belgium Phone: +32 1245 8330 Tianjin, China Fty 5, Ave. 9, TEDA Phone: +86 22 5981 3085